

High-Speed Overlock Machine

Bobjet -700-3D/4D/5D/6D



Computerized Direct Drive Motor

Direct drive servo motor with computerized speed controller reduces electricity usage by 70%.

Needle position

Choose whether the needle stops at the top or bottom after completing the seam.



Max Sewing Speed 6000 RPM (Adjustable)

Adjust the sewing speed digitally with the + and - keys.

Inbuilt LED Light

The LED light is integrated into the machine.



Fabric Cutter

The integrated small knife is useful for manually cutting the thread at the end of the seam.



Available Models



Three Thread with One needle
M 700-3D



Six Thread with three needles (Safety Stich)
M 700-6D



Five Thread with two needles (Safety Stich)
M 700-5D



Four Thread with two needles
M 700-4D

Specifications

| Model | Needle Type | No of Needles | Needle gauge (mm) | No of Threads | Stitch width (mm) | Stitch length | Presser Foot Lifting | Max Speed | Packing Size | N.W/G.W |
|---------------|-------------|---------------|-------------------|---------------|-------------------|---------------|----------------------|-----------|--------------|----------|
| Bobjet-700-3D | DCX27 11# | 1 | 2 | 3 | 4 | 0.5-3.8mm | 5.5mm | 7000RPM | 465*345*450 | 32/35KGS |
| Bobjet-700-4D | DCX27 11# | 2 | 2 | 4 | 4 | 0.5-3.8mm | 5.5mm | 6000RPM | 465*345*450 | 32/35KGS |
| Bobjet-700-5D | DCX27 14# | 2 | 3,5 | 5 | 5,8 | 0.5-3.8mm | 5.5mm | 6000RPM | 465*345*450 | 32/35KGS |
| Bobjet-700-6D | DCX27 14# | 3 | 3,5 | 6 | 5,8 | 0.5-3.8mm | 5.5mm | 6000RPM | 465*345*450 | 32/35KGS |